



Model	Size	L	H1	H2
RET-15-S	DN15	70	110	80
RET-20-S	DN20	85	115	105
RET-25-S	DN25	90	120	105
RET-40-S	DN40	115	130	130
RET-50-S	DN50	120	130	130

* Pressure Range : 1 kgf/cm² ~ 6 kgf/cm²
 4 kgf/cm² ~ 10 kgf/cm²
 8 kgf/cm² ~ 13 kgf/cm²

* Special order can be arranged for higher pressure adjustment range.

* Applied temperature : -15 °C ~ 80 °C

No	Parts Name	Materials	Standard
1	Gauge	-----	
2	Cover	Stainless Steel CF8M	ASTM-A351
3	O-Ring	EPDM	EP02971PWRC
4	U-Ring	EPDM	EP02971PWRC
5	Piston	Stainless Steel CF8M	ASTM-A351
6	Sealing spacer	EPDM	EP02971PWRC
7	Shaft	Stainless Steel CF8M	ASTM-A351
8	Main body	Stainless Steel CF8M	ASTM-A351
9	Diaphragm	EPDM	EP02971PWRC
10	O-Ring	EPDM	EP02971PWRC
11	UH-Ring	EPDM	EP02971PWRC
12	Spring	Spring Steel	
13	Spring cover	Stainless Steel CF8M	ASTM-A351
14	Washer	Brass	JIS-C3771
15	Adjusting stem	Stainless Steel #304	ASTM-A276



Z-Tide Valves

ELITE LINE INDUSTRIAL CORP.

Direct-Activated
 Pressure Reducing Valve
 PT-Threaded

Designed

Unit

Drwg. No

Proj. No

MM

RET-S

Checked

Date

27.Nov.14

-ACS

Thank you for evaluating Wondershare PDF Password Remover.

You can only convert 5 pages with the trial version.

To get all the pages converted, you need to purchase the software from:

<http://cbs.wondershare.com/go.php?pid=526&m=db>